


Equal tees

ASTM A403 / A815 ASME B16.9




● WP-S = made from seamless pipe
▲ WP-W = made from welded pipe or plate

Nominal pipe size	Schedule	Dimensions in mm D	C/M	Weight kg/pc	304L	316L	UNS S31803	UNS S32750
1/2"	10s	21.3	25.4	0.100	●/▲	●/▲	●	●
	40s	21.3	25.4	0.140	●/▲	●/▲	●	●
	80s	21.3	25.4	0.170	●	●	●	●
3/4"	10s	26.7	28.6	0.128	●/▲	●/▲	●	●
	40s	26.7	28.6	0.200	●/▲	●/▲	●	●
	80s	26.7	28.6	0.250	●	●	●	●
1"	10s	33.4	38.1	0.200	●/▲	●/▲	●	●
	40s	33.4	38.1	0.245	●/▲	●/▲	●	●
	80s	33.4	38.1	0.390	●	●	●	●
1 1/4"	10s	42.2	47.6	0.330	●/▲	●/▲	●	●
	40s	42.2	47.6	0.420	●/▲	●/▲	●	●
	80s	42.2	47.6	0.548	●	●	●	●
1 1/2"	10s	48.3	57.2	0.460	●/▲	●/▲	●	●
	40s	48.3	57.2	0.595	●/▲	●/▲	●	●
	80s	48.3	57.2	0.810	●	●	●	●
2"	10s	60.3	63.5	0.630	●/▲	●/▲	●	●
	40s	60.3	63.5	0.872	●/▲	●/▲	●	●
	80s	60.3	63.5	1.200	●	●	●	●
2 1/2"	10s	73.0	76.2	1.200	●/▲	●/▲	●	●
	40s	73.0	76.2	1.980	●/▲	●/▲	●	●
	160	73.0	76.2	3.170	●	●	●	●
3"	10s	88.9	85.7	1.450	●/▲	●/▲	●	●
	40s	88.9	85.7	2.410	●/▲	●/▲	●	●
	80s	88.9	85.7	3.250	●	●	●	●
3 1/2"	10s	101.6	95.3	1.550	●/▲	●/▲	●	●
	40s	101.6	95.3	2.950	●/▲	●/▲	●	●

Equal tees

ASTM A403 / A815 ASME B16.9



● WP-S = made from seamless pipe
▲ WP-W = made from welded pipe or plate

Nominal pipe size	Schedule	Dimensions in mm D	C/M	Weight kg/pc	304L	316L	UNS S31803	UNS S32750
4"	10s	114.3	104.8	2.460	●/▲	●/▲	●	●
	40s	114.3	104.8	4.130	●/▲	●/▲	●	●
	80s	114.3	104.8	7.110	●	●	●	●
5"	10s	141.3	123.8	4.040	●/▲	●/▲	▲	▲
	40s	141.3	123.8	6.550	●/▲	●	●	●
	80s	141.3	123.8	11.780	●	●	●	●
6"	10s	168.3	142.9	5.560	●/▲	●/▲	●/▲	●/▲
	40s	168.3	142.9	9.580	●/▲	●/▲	●	●
	80s	168.3	142.9	14.500	●	●	●	●
8"	10s	219.1	177.8	11.070	●/▲	●/▲	▲	▲
	40s	219.1	177.8	18.000	●/▲	●/▲	▲	▲
	10s	273.1	215.9	14.200	●/▲	●/▲	▲	▲
10"	10s	273.1	215.9	30.400	●/▲	●/▲	▲	▲
	40s	273.1	215.9	30.400	●/▲	●/▲	▲	▲
	80s	273.1	215.9	30.400	●	●	▲	▲
12"	10s	323.9	254.0	21.600	▲	▲	▲	▲
	40s	323.9	254.0	48.700	▲	▲	▲	▲
	10s	355.6	279.4	48.530	▲	▲	▲	▲
14"	STD	355.6	279.4	79.380	▲	▲	▲	▲
	10s	406.4	304.8	56.970	▲	▲	▲	▲
	40s	406.4	304.8	99.790	▲	▲	▲	▲
16"	STD	406.4	304.8	76.660	▲	▲	▲	▲
	10s	457.2	342.9	103.420	▲	▲	▲	▲
	40s	457.2	342.9	155.580	▲	▲	▲	▲
18"	10s	508.0	381.0	103.420	▲	▲	▲	▲
	40s	508.0	381.0	155.580	▲	▲	▲	▲
	10s	609.6	431.8	155.580	▲	▲	▲	▲